

NC SERIES TOWER CELLS

- NC Series Series Cooling Towers
 131 – 763 Tons
 Available in galvanized steel



	Tons*	HP	Dimensions				Shipping Weight (lb)	Design Operating Weight (lb)	Bottom Outlet Size
Galvanized Steel			L	W	H	A			
NC8301C.....	131	5	6'-5"	14'-0"	10'-2"	6'-8"	4,528	9,116	8"
NC8301DL.....	150	7.5	6'-5"	14'-0"	10'-2"	6'-8"	4,528	9,116	8"
NC8301EL.....	167	10	6'-5"	14'-0"	10'-2"	6'-8"	4,528	9,116	8"
NC8302D.....	184	7.5	7'-11"	15'-6"	10'-2"	8'-2"	4,999	11,256	8"
NC8302E.....	204	10	7'-11"	15'-6"	10'-2"	8'-2"	4,999	11,256	8"
NC8302FL.....	229	15	7'-11"	15'-6"	10'-2"	8'-2"	4,999	11,256	10"
NC8303DL.....	204	7.5	7'-11"	15'-6"	11'-11"	8'-2"	5,765	12,022	8"
NC8303E.....	229	10	7'-11"	15'-6"	11'-11"	8'-2"	5,765	12,022	10"
NC8303FL.....	259	15	7'-11"	15'-6"	11'-11"	8'-2"	5,765	12,022	10"
NC8303G.....	284	20	7'-11"	15'-6"	11'-11"	8'-2"	5,765	12,022	10"
NC8304D.....	270	10	8'-11"	17'-0"	13'-0"	9'-2"	7,024	14,699	10"
NC8304E.....	310	15	8'-11"	17'-0"	13'-0"	9'-2"	7,024	14,699	10"
NC8304F.....	339	20	8'-11"	17'-0"	13'-0"	9'-2"	7,024	14,699	12"
NC8304G.....	362	25	8'-11"	17'-0"	13'-0"	9'-2"	7,024	14,699	12"
NC8305E.....	263	15	10'-11"	18'-9"	13'-0"	11'-2"	9,191	19,486	12"
NC8305F.....	403	20	10'-11"	18'-9"	13'-0"	11'-2"	9,191	19,486	12"
NC8305G.....	431	25	10'-11"	18'-9"	13'-0"	11'-2"	9,191	19,486	12"
NC8305H.....	453	30	10'-11"	18'-9"	13'-0"	11'-2"	9,191	19,486	12"
NC8306F.....	441	20	11'-11"	19'-10"	13'-0"	12'-2"	11,156	22,969	14"
NC8306G.....	474	25	11'-11"	19'-10"	13'-0"	12'-2"	11,156	22,969	14"
NC8306H.....	503	30	11'-11"	19'-10"	13'-0"	12'-2"	11,156	22,969	14"
NC8306J.....	557	40	11'-11"	19'-10"	13'-0"	12'-2"	11,156	22,969	14"
NC8307G.....	502	25	11'-11"	22'-5"	13'-4"	12'-2"	12,198	27,256	14"
NC8307H.....	532	30	11'-11"	22'-5"	13'-4"	12'-2"	12,198	27,256	14"
NC8307J.....	582	40	11'-11"	22'-5"	13'-4"	12'-2"	12,198	27,256	16"
NC8307K.....	622	50	11'-11"	22'-5"	13'-4"	12'-2"	12,198	27,256	16"
NC8307M.....	651	60	11'-11"	22'-5"	13'-4"	12'-2"	12,198	27,256	16"



continued from spec. page #1

	Tons*	HP	Dimensions				Shipping Weight (lb)	Design Operating Weight (lb)	Bottom Outlet Size
			L	W	H	A			
Galvanized Steel									
NC8309CL.....	481	15	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	12"
NC8309D.....	532	20	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	14"
NC8309E.....	575	25	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	14"
NC8309F.....	609	30	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	14"
NC8309FL.....	603	30	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	14"
NC8309G.....	663	40	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309GL.....	661	40	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309H.....	702	50	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309HL.....	696	50	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309J.....	741	60	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309JL.....	739	60	13'-11"	22'-5"	13'-4"	14'-2"	14,501	32,097	16"
NC8309K.....	765	60/stk	13'-11"	22'-5"	16'-10"	14'-2"	14,665	32,261	16"
NC8309KL.....	763	60/stk	13'-11"	22'-5"	16'-10"	14'-2"	14,665	32,261	16"

- Nominal tons are based on 3 GPM /Ton cooled from 95°F to 85°F at a 78°F wet bulb.

